

**IDIT Droppslang PE 16 mm x
1,15 mm 46mil 4bar 130mikron
2,3L/h 30cm svart 25m type
Non PC (7010230)**



TEKNISKA SPECIFIKATIONER

Färg svart

Typ Non PC

Material PE

Filtrering 130 mikron

Filtrering 120 mesh

Tryck 4 bar

Rek. tryck 2 bar

Vägg tjocklek 46 mil

Vägg tjocklek 1,15 mm

Flow 2,3 L/h

Storlek 16 mm

Längd 25 m

Inner Ø 13,7 mm

Max längd 59 m

Avstånd 30 cm

IDIT					
Bar	Q = L/H - IDIT 16-1,4 bar	Q = L/H - IDIT 16-2,3 bar	Q = L/H - IDIT 16-3,3 bar	Q = L/H - IDIT 16-4,3 bar	Q = L/H - IDIT 16-10 bar
0,5	0,9	1,5	2,0	2,8	6,5
1,0	1,3	2,1	2,9	4,0	9,3
1,5	1,6	2,6	3,6	4,9	11,5
2,0	1,9	3,1	4,1	5,7	13,3



bevo
bringing water to life

PRODUKTINFORMATION

Droppledningar, korta spolar, speciellt för mindre installationer.

Genererad den: 05/11/2025

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>