

Tavlit Automatisk filterstation fiberglasförstärkt nylon 2" 10bar 105mikron disk 9-12VDC latch svart type TADSA Stand Alone (7031297)



TEKNISKA SPECIFIKATIONER

Färg	svart
Typ	TADSA
Material	fiberglasförstärkt nylon
Material filterelement	disk
Packningsmaterial	EPDM
Backspolnings flow rate	6,5 m ³ /h
Typ	Stand Alone
Längd	1050 mm
Volt	9-12VDC latch
Bredd	310 mm
Höjd	1080 mm
Min. inloppstryck	1.5 bar
Tryck	10 bar
Kapacitet	20 m ³ /h
Filtrering	105 mikron
Storlek	2"
Filteryta	1100 m ²

PRODUKTINFORMATION

TADSA automatic disc filtration stand alone unit.

When the head loss reaches a preset value of 0.5b-0.7b, the controller starts flushing one filter after the other.

Flushing cycle will take from 12 to 30 seconds depending on the dirt load.

During flushing the flow to the field is uninterrupted.

Minimum flushing pressure required: 2.5bar.

Flushing flow rate: 9.3m³/h.

Components: Talgil controller, 2" Bermad backflush valves and PE manifolds.

Genererad den: 08/11/2025

Bevo Nordic A/S
Pakhusgården 54
5000 Odense C
Danmark
+45 66 19 25 45
info@bevo.dk
<http://www.bevo.com>